

ELECTRIC VEHICLE CHARGING STATION CONFIGURATIONS

PRACTICAL MULTI-PORT CHARGING FOR COMMERCIAL PARKING FACILITIES

MODEL EVSE-RS SINGLE, DUAL AND QUAD

FEATURES

- Industry standard SAE-J1772 connector
- Underwriters Laboratory (UL) listed
- Outdoor rated enclosure
- Americans with Disabilities Act (ADA) compliant installation
- Auto restart in event of power outage or ground fault
- Breakaway safety cable
- Integrated cable stowage
- Optional network communication module (EVSE-RS+)

SERVICE AND INSTALLATION

- Expanding network of independent certified, trained electricians
- Convenient customer site assessments and installation
- 24-hour response time during business hours



The safe, reliable EVSE-RS Charging Station is available in single port, dual-port and quad-port configurations for higher-traffic commercial and public charging applications. While maintaining the same user friendly design of the single-port unit, the EVSE-RS Dual and Quad systems can simplify the installation and reduce costs by consolidating wiring runs and mounting locations. The attractive, weather-resistant housing provides a polished look that complements professionally maintained properties such as car dealerships, multi-dwelling units, shopping malls, corporate offices, and retail stores.

EVSE-RS multiport systems are compatible with all SAE J1772 compliant electric vehicles (EVs) and plug-in hybrids (PHEVs). Each charge port complies with all features and specifications of the single-port EVSE-RS, and an optional module for Ethernet, WiFi, Zigbee, or cellular communication is available.

SPECIFICATION	EVSE-RS
Connector	SAE J1772 compliant
Voltage	208VAC to 240VAC
Frequency	60/50Hz
Output Current	30A max
Input Current	40A max
Operating Temperature	-22°F to 122°F -30°C to 50°C
Enclosure	NEMA 3R
Regulatory Compliance	UL, cUL, CE, CTick listed

Information and specifications subject to change.

